
P700

FAST • ON-DEMAND • COLOUR LABELS

The **VP700 by VIPColor** is a revolutionary digital print-on-demand colour label printer • Set to reinvent printing and raise the performance benchmark for printers in its class.

Powered by Memjet thermal inkjet technology, the VP700 prints at a blazing speed of 18 metres per minute (or 100 10 cm x 15 cm labels in less than a minute), delivering exceptional vibrant colour graphics and crisp text and barcodes up to 1600 x 1600 dpi*. The VP700 prints on demand to exact batch quantity and real-time up-to-the-minute requirements, providing unprecedented flexibility and convenience. Ruggedly designed yet intuitive for use in in-house label production and private labeling needs, the VP700 brings fast, affordable colour printing to any print environment.

Key Benefits



only

* For Memiet ink compatible label stock, we strongly recommend that the user perform a print check for compatibility before using the label stock for production





VP700

Printer Specifications

PERFORMANCE

| Print speed | Up 304,8 mm per second (18 m/minute, or 12 ips) |
|----------------------------|--|
| Print resolution | Up to 1600 x 1600 dpi |
| Data connectivity | USB 2.0 / Ethernet 10/100Base-T / GPIO |
| Ink | Dye ink in five individual 250 ml CYMKK colour ink tanks |
| Power supply Barcode PQ | Universal internal power supply 1D barcode at least Grade B (Code 39) with 10mils bar width 2D barcode at least Grade B (PDF417) with 10mils cell size |

MEDIA HANDLING

| Print modes | Roll-Roll, Roll-Cut, Print & Hold (non-peel) |
|------------------------|---|
| Label media width | 50,8 - 215,9 mm (2" - 8,5") |
| Max. label length | Up to 1,016 m (40") |
| 5 | |
| Label media thickness | 0,1 - 0,3 mm |
| Supported media | Glossy , Semi-Gloss and matte |
| Qualified label stocks | Please, check the compatibility list of VIPColor printers |
| Detection | Gap, continuous, black mark |

OPERATING ENVIRONMENT

Operation 15 to 35°C at RH 20-80% Storage -5 to 50℃

REGULATORY & SAFETY

EMC Safety FCC Part 15, Subpart B, Class A (US), CE (Europe), BSMI (Taiwan) IEC 60950-1 Compliance (International), RCM (Australia), CCC (China), cCSAus (US/Canada)

USABILITY & SERVICEABILITY

| User interface | Embedded web server |
|------------------------------|---|
| | Backlit LCD control panel in 8 languages (EN, FR, DE, IT, ES, JP, CN Traditional & Simplified) |
| | LED for printer warnings & readiness indication |
| | Unobstructed accessbility to service bays for print-head and ink tanks |
| Aesthetics | Designed for ease of setup, troubleshooting and servicing |
| | Metallic casing with industrial grade ruggedness |
| Printer driver compatibility | Microsoft® Windows XP/Vista®/Windows 7 (32/64bits); Windows |
| | Server 2003/2008 R2 (32/64 bits) |
| Supported network protocol | TCP/IP (Static IP or DHCP Auto) |
| Acoustics | Sound pressure level less than 60dBA (both operator/ bystander position) |

ACCESSORIES & OTHERS

| Built-in accessories | Integrated un-winder (with enclosure for paper dust removal) as standard for up to 200 mm (8") OD label roll with 76 mm (3") core. Built-in automatic cutter. |
|-----------------------|---|
| Product size | 476 mm x 497 mm x 585 mm (18,7" x 19,6" x 23,0") |
| Weight (printer only) | 35 kg (77 lbs) |
| Warranty | 1 year limited factory warranty or 5M inches - whichever comes first |


SHIPPED

Included items

Printer (integrated with un-winder), CD (driver + manual), printhead, CMYKK ink cartridges, USB cable and AC power cable

Note:

- The technical specifications & suggested pricings are subjected to change without notice.
 Barcode PQ is dependent on label media compatibility with the ink.
 Limited warranty does not include consumables, ink supplies and printhead.
 * Windows is a registered trademark of Microsoft Corporation in the United States and other countries.





Pagesia, 22-24 1-B 08191 - Rubí (Barcelona) SPAIN