
LABELMATE

# LD-100-U & LD-200-U

## Universal Powered Label Dispensers

## For All Labels Including Transparent and Black Labels



*LD-100-U*

**The LD-U Type Automatic Label Dispensers uses a new "state of the art" reflective detector that allows the machine to dispense all types of labels, including transparent and black labels.**

The **LD-U** range is using a compact photoelectric sensor with optic-fibre cable. The **LD-100-U** and **LD-200-U** offer the same advantages, convenience and durability as the popular LD-RS models with the extra benefit of dispensing any kind of labels.

The **LD-100-U-SS** and **LD-200-U-SS** feature a stainless steel chassis and cover and can be used in humid environment. They are ideal for food industry and pharmaceutical applications.

All LABELMATE Label Dispensers are easy to set up, too. You just slide your roll of labels onto the built-in Core Holder. Then thread the label web through to the take-up spindle and your Label Dispenser is ready for use! Rugged, heavy-gauge steel construction and precision parts yield products of the highest quality. Designed for all-day, every-day use, these Dispensers are backed by LABELMATE's famous 3-Year Parts and Labour Limited Warranty, assuring you trouble-free performance.

| MODEL | DESCRIPTION | LABEL WIDTH (mm) | LABEL LENGTH (mm) | ROLL DIAM. (mm) | SPEED (cm/sec) |
|---|---|---|---|---|---|
| **LD-100-U** | Automatically advances the next label ready to pick. Fast label loading. Quick and convenient operation! For transparent and black labels. | Up to 115 | 10 to 150*<br>20 to 150* for transparent | 220 | 11<br>Minimum |
| **LD-200-U** | Same features as LD-100-U but with wider label capacity. | Up to 165 | 10 to 150*<br>20 to 150* for transparent | 220 | 11<br>Minimum |
| **LD-100-U-SS** | Same features as LD-100-U but in stainless steel. | Up to 115 | 10 to 150*<br>20 to 150* for transparent | 220 | 11<br>Minimum |
| **LD-200-U-SS** | Same features as LD-200-U but in stainless steel. | Up to 165 | 10 to 150*<br>20 to 150* for transparent | 220 | 11<br>Minimum |

*** Depending on the labels.**

**The World's Leading Manufacturer of Label Dispensers, Rewinders, Unwinders, Slitters and Core Chucks**
**LABELMATE LLC, 69 Avenue Alphonse XIII, B-1180 Brussels, Belgium**
**Tel. +32 2 375.69.60 FAX +32 2 375.38.96**
**www.labelmateeuropeeurope.com E-mail: brussels@labelmate.com**


# LABEL DISPENSERS OPTIONS

| MODEL | DESCRIPTION | ROLL DIAM. (mm) | SPEED (cm/sec) |
|---|---|---|---|
| **C-1** | Counter option for Label Dispenser (factory installed). | - | |
| **LD-FLANGES-220** | Inner and outer Flange option for Label Dispenser (per pair). Fits all models.<br>Recommended for narrow labels. | 220 | |
| **LD-FLANGES-300** | Inner and outer Flange option for Label Dispenser (per pair). Fits all models. To be used with LD-DE.<br>Recommended for narrow labels. | 300 | |
| **PS-18V** | High-speed power supply to increase speed of the dispenser. | - | 14 min. |
| **LD-DE** | Diameter extension: Allows using rolls with outer diameters up to 300mm (factory installed). | 300 | |
| **EXT. COMMAND** | The LD dispenses one label when receives a signal (contact closure). Factory installed. | - | |
| **BATTERY PACK** | Complete kit to operate the LD on a battery. Includes: battery, charger and cables. Replace the standard power supply. Battery works for +/- 8 hours and needs 8 hours to re-charge.<br>Output: DC 12V. | - | - |

**Size:** H x W x D Approximately 229-x 305-x 229-mm.
**Shipping Weight:** Approximately 6.4- to 6.8-kg.
**Power:** 230-vac 50-Hz 40-va. 120-vac 60-Hz power supply is also available.




*Compact Photoelectric Sensor*



*LD-100-U with Flanges*

Specifications are subject to change without notice. DataLDU EUR 09/2012

**The World's Leading Manufacturer of Label Dispensers, Rewinders, Unwinders, Slitters and Core Chucks**
**LABELMATE LLC, 69 Avenue Alphonse XIII, B-1180 Brussels, Belgium**
**Tel. +32 2 375.69.60 FAX +32 2 375.38.96**
**www.labelmateeuropeeurope.com E-mail: brussels@labelmate.com**